



EG-Typgenehmigung:  
EC-type approval:

**e11 00 - 6289**

ECE-Typgenehmigung:  
ECE-type approval:

**E11 55R - 01 6289**

Klasse gemäss ECE 55-01:  
Class according to ECE 55-01:

nicht genormte, selbsttätige Bolzenkupplung C50-X  
non standard automatic drawbar coupling C50-X

Nur zur Verbindung mit Zugösen:

D50 gemäss Richtlinie 94/20 EG oder ECE 55-01 sowie Zugösen 50 DIN 74053 und Zugösen nach ISO 1102 sowie Schwerlast-Zugösen 50mm (Ringfeder Best. Nr. 6991394 oder baugleiche)

Only suitable for connection with drawbar eyes:

D50 in accordance with the directive 94/20 EC or ECE 55-01 and drawbar eyes 50 acc. to DIN 74053 or acc. to ISO 1102 and heavy duty drawbar eyes 50mm ( Ringfeder order no. 6991394 or equal)

Winkelausschläge der Zugöse D50:  
angles of drawbar eye D50:

horizontal: ± 110°  
vertikal: ± 20°  
axial: ± 360° bei einem Mindest-Drehmoment von 100 Nm  
if using minimum tightening torque of 100 Nm

D:	200 kN	200 kN	200 kN
Dc:	135 kN	135 kN	135 kN
S:	1000 kg	2000 kg	2500 kg
V:	75 kN	63 kN	50 kN

VBG GROUP		Modified Date	Modified by	PU-number	Issue
		13.02.2014	HBH	11804	a
		3D-Model No.	Checked by	Engineer	Signed by
		14996217	RB		
		Sheet Size	Scale	Projection	Drafting Date
		A2	1:4	FF	28.11.2005
		Foreign Drawing No.			
		Description Name			
		Automatic drawbar coupling			
		Selbsttätige Bolzenkupplung			
		Type 5050 B			
Mass	Surface treatment				
48 kg	see note 1				
		Stage	Drawing No.		
			14996217-info		
		Remark		Id. No.	

This drawing is the property of VBG Group AB and is protected in accordance with prevailing law. Changes must be made in CAD-program, this concerns both 2D & 3D.